

Ambu® BlueSensor L

ECG Electrode - Single use



Key Benefits

- Highly conductive wet gel
- Combination of instant and long-term adhesives
- Breathable microporous material
- Unique offset connector
- High-quality Ag/AgCl sensor

Ambu® BlueSensor L

The large Ambu BlueSensor L features highly conductive wet gel, offset connector and a combination of instant and long-term adhesives for excellent contact and stable signals throughout the monitoring period.

Thanks to the low-profile microporous material, skin is able to breathe so the electrode remains comfortable to wear over long periods.



Wet gel



Microporous
backing

BlueSensor

Ambu 
Ideas that work for life

Specifications

Dimensions	
Electrode size (L x W in mm)	68.2 x 55
Skin contact size (L x W in mm)	55
Adhesive area (in mm ²)	2121
Height excluding connector/wire (in mm)	1
Sensor	
Sensor material	Silver/silver chloride
Gel system	Wet gel
Sensor area (in mm ²)	20.8
Gel area/measuring area (in mm ²)	254
Electrical data (ANSI/AAMI)	
AC impedance - typical	500 Ω
DC offset voltage - typical	0.2 mV
Defibrillation overload recovery - typical	7.4 mV
Rate of change of polarization potential	0.2 mV/s
Combined offset instability and internal noise	<15 µV
Bias current tolerance (over 8 hours)	<5 mV

Environment	
PVC-free electrode	No
Electrode not made with natural rubber latex	
PVC-free lead wire	-
Wire not made with natural rubber latex	
PVC-free packaging	Yes
X-Ray & MRI	
Radiolucent	No
MR Conditional	No
Shelf life	
Opened pouches	1 month
Unopened pouches*	24 months

*from date of production

Connectors



S = Stud



A = 4 mm fitting

Materials

Electrode	
Bio-compatible	Yes
Sensor	Silver/silver chloride (Ag/AgCl)
Sponge	Polyurethane foam (PUR)
Outer carrier	Microporous tape (non-woven rayon)
Outer adhesive	Acrylate
Inner carrier (if any)	Polyvinyl chloride film (PVC)
Inner adhesive (if any)	Acrylate
Upper part	Polyvinyl chloride film (PVC)
Fitting	Polypropylene (PP)
Connector (stud)	Nickel-plated brass
Lead wire core	-
Lead wire insulation	-
Lead wire connector	-
Liner	Polyester/polyethylene film (PET/PE)

Packaging	
Pouches, inner layer	Polyethylene (PE)
Pouches, centre layer	Aluminium (Al)
Pouches, outer layer	Polyester (PET)
Boxes	Cardboard
Standard Packaging	
Quantity/liner	1
Quantity/pouch	5, 25
Quantity/box	500/1000
Minimum sales	1000

Options	
Connectors	S, A
Pre-wired	-
Pre-wired connectors	-
Precaution	
Single use only	

Available configurations*

Quantity/pouch	5	25
	Quantity per inner/outer box	
L-00-S	500/1000	500/1000
L-00-A		500/1000

- Product
- Wire length
- Connector

*some configurations may not be available worldwide

Ambu A/S
 Baltorpbakken 13
 DK - 2750 Ballerup
 Denmark
 Tel. +45 7225 2000
 Fax +45 7225 2053
 www.ambu.com